

## Specification Summary

Series	Voltage (V)	Current (A)	Contacts	IP	EMI	OD (mm)	Termination				Locking Style				
							Sloder	PCB	Crimp	Screw	Threaded	Bayonet	Snap-in	Push-pull	
<b>Subminiature Connectors and Cordsets</b>															
<b>620</b>	125	1-3	3-8	67		11.5	✓						✓		
<b>702</b>	Cordset with <b>Series 711</b> connectors														
<b>709</b>	Cordset with <b>Series 719</b> connectors													✓	
<b>710</b>	125	1-4	2-8	40		12.0	✓					✓			
<b>711</b>	125	1-4	2-8	40	✓	11.5	✓	✓			M9x.5				
<b>712</b>	125	1-4	2-8	67	✓	11.5	✓	✓			M9x.5				
<b>719</b>	60	3	3-5	40		8.0	✓	✓					✓		
<b>Miniature Connectors and Cordsets</b>															
<b>423</b>	60/250	1-7	2-24	67	✓	18.5	✓	✓			M16x.75				
<b>425</b>	Cordset with <b>Series 423</b> connectors														
<b>440</b>	60/250	1-7	2-19	67	✓	20.0	✓							✓	
<b>581</b>	60/250	1-7	2-24	40	✓	18.5	✓	✓			M16x.75				
<b>678</b>	60/250	1-7	2-24	40		20.0	✓					✓			
<b>680</b>	60/250	1-7	2-24	40		17.0	✓	✓			M16x.75				
<b>682</b>	60/250	1-7	2-24	40	✓	19.0	✓	✓			M16x.75				
<b>720</b>	60/250	2-7	3-24	67		16.0	✓						✓		
<b>723</b>	60/250	1-7	2-24	67		21.5	✓				M16x.75				
<b>Industrial Connectors</b>															
<b>623</b>	60/250	7.5-16	6-19	67	✓		✓				M23x1				
<b>690</b>	125/250	5-10	3-12	40			✓					✓			
<b>691</b>	125/250	5-10	3-12	40			✓				M25x1				
<b>693</b>	250/400	10-16	3-7	67			✓		✓	✓	RD 24				
<b>694</b>	60/400	3-20	5-24	65			✓			✓	RD 30				
<b>Automation and Sensor Interconnects</b>															
<b>707</b>	125	1	3-4	67		6.0	✓				M5x.5				
<b>713</b>	60/250	2-4	3-8	67	✓	20.0	✓	✓			M12x1				
<b>715</b>	125/250	4	4-5			20.0					M12x1				
<b>718</b>	Cordset with <b>Series 768</b> connectors														
<b>763</b>	Cordset with <b>Series 713</b> connectors														
<b>766</b>	Cordset with <b>Series 715</b> connectors														
<b>768</b>	60	4	4-5	67	✓	12.0	✓			✓	M8x1				
<b>815</b>	250	4	3	67		20.0	✓			✓	1/2"				
<b>820</b>	250	9-12	2-4	67		27.0				✓	7/8"				
<b>825</b>	250	4	4	67	✓	20.0				✓	M12x1				
<b>876</b>	Cordset with <b>Series 825</b> connectors														
<b>772</b>	10/30	2		67							M8/M12				
<b>775</b>	10/30	4		67							M12				
<b>Solenoid Valve Connectors</b>															
<b>M-A</b>	24/250	2-10					✓			✓					
<b>M-B</b>	24/250	2-10					✓			✓					
<b>M-C</b>	24/250	2-10					✓			✓					